

B DISPENSERS BATTERY KIT



EN. Portable diesel transfer unit. Self-priming electric vane pump run by a 12V or 24 V DC electric motor. Cast iron body. Fixed brush motor with permanent magnet stator. Suction capacity up to 6.5 feet. Terminal board with switches and fuses to protect against overload. 6.5 ft. cables with clips for battery connection. 13 ft. fuel pipe, diameter 3/4". Aluminum manual nozzle. Bottom suction filter.

ES. Unidad móvil para el trasiego de gasolina. Electrobomba auto cebante de paletas con motor de 12V ó 24V y electricidad DC. Estructura de hierro fundido. Motor de escobillas con estator de imanes permanentes. Capacidad de aspiración de hasta 2 metros. Caja de conexiones con interruptor y fusible para protección de sobrecargas. Cables de 2 metros con pinzas de conexión a la batería. Tubo de 4 metros para carburantes, de 3/4" de diámetro. Pistola manual de aluminio. Filtro de pie para tubo de aspiración.

PT. Grupo portátil para transferência de gásóleo. Electrobomba de palhetas autoescorvante com motor de 12 ou 24 Vdc de corrente continua. Corpo de ferro gusa. Motor de escovas com estator de magnetes permanentes. Capacidade de aspiração de até 2 metros. Caixa de bornes com interruptor e fusível para proteção contra sobrecarga. Cabos de 2 metros com grampos para prender a uma bateria. Tubo de 4 metros para carburante, de 3/4" de diámetro. Pistola manual de alumínio. Filtro no fundo para tubo de aspiração.

PERFORMANCE

- 12 - 24 V DC operation
- Duty cycle 30 min.

- Caudal hasta 50 l/min
- Funcionamiento 12V - 24V DC
- Ciclo de funcionamiento 30 min.

- Caudal até 50 l/min
- Funcionamento 12 - 24 V DC
- Ciclo de trabalho 30 min.

Flow rate

up to
12
gpm

2 YEAR WARRANTY

PRODUCTS' RANGE WEIGHT AND PACKAGING

Part #	Weight		Packaging		
	kg	lbs	mm	inch	pcs/box
BATTERY KIT 3000					
FOO225OOC	7.8	17.3	305x305x178	12x12x7	1
FOO226OOC	7.8	17.3	305x305x178	12x12x7	1

FEATURES

Handle



On/Off switch



Automatic nozzle



DRUM KIT



ON REQUEST

PRODUCTS' RANGE TECHNICAL DATA

Part #	Description	Fluids type	Flow rate		Voltage			Fuses capacity	Pump mod.	Duty cycle min.	Nozzle type	Hose		Foot filter
			l/min	gpm	AC V/Hz DC Volt	Power Watt	Amp. max.					length	Ø	
BATTERY KIT 3000														
FOO225OOC	BATTERY KIT 3000 12V	D	50	12	12	260	22	25	Carry 3000	30	Man.	13 ft	3/4"	YES
FOO226OOC	BATTERY KIT 3000 24V	D	50	12	24	310	13	15	Carry 3000	30	Man.	13 ft	3/4"	YES