



DT-MOBILE EASY

Innovative diesel filling stations offering a wealth of useful features.



Adjustable lid mount

The adjustable lid mount allows it to be installed either on the left or the right for the best possible access (460 L and 600 L).



Video
DT-Mobile Easy



Nozzle holder

The built-in holder secures the nozzle during transport.



Built-in ergonomic carry handles

The built-in carry handles enable the equipment to be handled easily during loading.



Integral forklift pockets

The integral forklift pockets make handling easier when the tank is full.

Technical specifications subject to change.



Built-in hose brackets

The built-in hose brackets keep things tidy until you next need to fill up.



Integrated ventilation with pressure relief

The integrated vent system means that fuel can be dispensed continuously without the container needing to be opened.



Delivery line can be shut off

The isolation valve enables the container to be sealed off completely, thus adding to safety during transportation (125 L, 200 L, 460 L, 600 L, 850/100 L and 980 L).



Recesses for ratchet lashing strap

Integral recesses (125 L, 200 L, 210 L and 440 L) and lashing eyes (460 L, 600 L, 850 L/100 L and 980 L) to allow immobilisation with a ratchet lashing strap during transportation.



Folding crane eye and lashing eyes

The folding crane and lashing eyes (460 L, 600 L, 850 L/100 L and 980 L) make it easier to secure the load in the prescribed manner, and serve at the same time as fastening eyes if the device is lifted by crane.



DT-MOBILE EASY 200, 460 AND 600 L PG 4

WITH ADR APPROVAL

TOP SELLER

SP package DT-Mobile Easy 200 litre with CENTRI-pump

- capacity 200 litre
- submersible pump CENTRI SP 30, 12 V, 30 L/min
- automatic nozzle

Order no. 10735

with ADR approval



CENTRI SP 30
EXTREMELY
QUIET

DT-Mobile Easy with ADR approval

Approved for transport under ADR Examination every 2 ½ years according to ADR 6.5.4.4.1 b) and ADR 6.5.4.4.2 b).*** Completely assembled.

Container:

- 200 L, 460 L or 600 L polyethylene, single-walled
- with hinged lid (200L version)
- with crane eyes (460 L and 600L version)
- integral nozzle holder
- integral filling nozzle
- integrated vent with pressure relief
- integral forklift pockets and handles
- integral recesses (200L) or loops (460 L and 600 L) for securing the trolley with ratchet straps during transport

Pre-fitted pump:

- self-priming, pump 12V or 24VDC, 2.5 or 40 L/min, with automatic nozzle or manual nozzle, 4 m filling hose DN 19 and 4 m electrical cable
- submersible pump CENTRI SP 30, 12 V, 30 L/min, extremely quiet, with automatic nozzle, 4 m filling hose DN 19 and 4 m electrical cable
- hand pump 25 L/min, 2.7 m filling hose DN 19 and manual nozzle

*** Transport approval for all IBC plastics is limited to a life of 5 years. The 200 L model is therefore also approved for transport for direct consumption under ADR 1.1.3.1 c).

with ADR approval



DT-Mobile Easy 600 L
with electric pump,
automatic nozzle
and hinged lid

DT-MOBILE EASY WITH ADR APPROVAL

Description	Capacity L	Dimensions in cm (l x w x h)	Weight approx. kg	Order no.
200 with hand pump, manual nozzle and hinged lid	200	80 x 62 x 61	26	10080
200 with submersible pump CENTRI SP 30, 12 V, 30 L/min, automatic nozzle and hinged lid	200	80 x 62 x 61	24	10735*
200 with pump 12 V, 40 L/min, automatic nozzle and hinged lid	200	80 x 62 x 61	28	10083
200 with pump 24 V, 40 L/min, automatic nozzle and hinged lid	200	80 x 62 x 61	28	10112
460 without pump, with quick coupling for vehicles with integrated suction pump	460	116 x 80 x 81	42	10415
460 with pump 12 V, 40 L/min and automatic nozzle	460	116 x 80 x 81	47	10416
460 with pump 24 V, 40 L/min and automatic nozzle	460	116 x 80 x 81	47	10417
460 with pump 12 V, 40 L/min, automatic nozzle and hinged lid	460	116 x 80 x 86	60	10418
460 with pump 24 V, 40 L/min, automatic nozzle and hinged lid	460	116 x 80 x 86	60	10419
600 without pump, with quick coupling for vehicles with integrated suction pump	600	116 x 80 x 102	48	10084
600 with pump 12 V, 40 L/min and automatic nozzle	600	116 x 80 x 102	53	10085
600 with pump 24 V, 40 L/min and automatic nozzle	600	116 x 80 x 102	53	10086
600 with pump 12 V, 40 L/min, automatic nozzle and hinged lid	600	116 x 80 x 107	66	10087
600 with pump 24 V, 40 L/min, automatic nozzle and hinged lid	600	116 x 80 x 107	66	10088

Technical specifications subject to change.



DT-MOBILE EASY 980 L AND COMBI 850/100 L PG 4 WITH ADR APPROVAL

Approved for transport under ADR Examination every 2 ½ years according to ADR 6.5.4.4.1 b) and ADR 6.5.4.4.2 b).***
completely assembled

- integral handles
- with crane eyes
- with flap lid
- integral loops for securing the trolley with ratchet lashing strap during transport

COMBI versions with additional tank for AdBlue®: with submersible pump CENTRI SP30, 12 V, 5 m filling hose DN 19 and automatic nozzle

Container:

- 980 L polyethylene, single-walled (diesel tank)
- 850/100 L polyethylene, single-walled (diesel/AdBlue® tank)
- integral baffle
- integral dispensing nozzle holder
- integral filling nozzle
- integral vent and pressure relief
- integral forklift pockets

Basic versions:

with powerful electric pump, 4 m filling hose DN25 (without hose reel, meter and filter) and automatic nozzle

Premium versions:

with powerful electric pump, hose reel with 8 m hose DN25, flow meter, filter with water separator and automatic nozzle

Pump options:

- Bipump 12 V, 500 W, approx. 85 L/min*
- pump Cematic Duo 24/12 V, 420 W, approx. 70/35 L/min*
- pump Cematic 72, 230 V, 500 W, approx. 72 L/min*
- submersible pump CENTRI SP30, 12 V, 220 W, approx. 25 L/min*
- hand pump 60 L/min*



DT-Mobile Easy 980 without pump, with quick coupling



DT-Mobile Easy 980 Basic



DT-Mobile Easy 980 with hand pump



DT-Mobile Easy COMBI 850/100 Premium



DT-Mobile Easy 980 Premium

DT-MOBILE EASY 980 L WITHOUT PUMP OR WITH HAND PUMP

Description	Capacity L	External Dimensions cm (l x w x h)	Weight approx. kg	Order no.
980 without pump with quick coupling	980	127 x 107 x 112	95	10817
980 with hand pump 60 L/min, 4 m filling hose DN 19, manual nozzle	980	127 x 107 x 112	100	11025

DT-MOBILE EASY 980 L DIESEL TANK

Description	Capacity L	External Dimensions cm (l x w x h)	Weight approx. kg	version electric pump		
				Bipump 12 V Order no.	Cematic Duo 24/12 V Order no.	Cematic 230 V Order no.
980 Basic	980	127 x 107 x 112	107	10818	10822	10826
980 Premium	980	127 x 107 x 112	130	10819	10823	10827

DT-MOBILE EASY COMBI 850/100 L DIESEL-/ADBLUE®-TANK

Description	Capacity L	External Dimensions cm (l x w x h)	Weight approx. kg	electric pump version diesel (AdBlue: CENTRI SP30 12 V)		
				Bipump 12 V Order no.	Cematic Duo 24/12 V Order no.	Cematic 230 V Order no.
850/100 Basic	850/100	127 x 107 x 112	121	10820	10824	10828
850/100 Premium	850/100	127 x 107 x 112	143	10821	10825	10829

* Pump output in free flow. Please note that the pump output can fall sharply depending on the length and cross-sectional area of the hose.

*** Please note that transport approval for all plastic IBCs is limited to a period of 5 years.